



Mobile Electric Boilers 9, 22 & 42 kW

Värmebaronen's mobile electric boilers are complete, transportable and are available in 9, 22 and 42 kW.

The boilers can be used as temporary or permanent sources of heat for both planned and unplanned events. Renovation, new constructions, drying foundations, when a heating plant is to be replaced or before permanent connection to the ordinary electricity grid. The power is divided into several steps for high comfort levels and good economy.

The boilers are fully equipped with a temperature control, level switch, circulation pump, expansion tank, safety equipment, and a power intake with CEE connector.

22 & 42 kW

Weight 110 kg
 Volume 18 litres
 Safety valve, 3 bar
 Connection: claw coupling
 (or 1"/R25 ext.)
 Temp 20-95 degrees
 Power: Max 22kW or 42 kW (can be stepped down to 15 or 24 kW respectively)
 Voltage 400 V 3N~ 50 Hz
 Current: 32 A/63 A
 Fuse: 3 x 32 A or 3 x 63 A
 IP class: IP 44

9 kW

Weight 30 kg
 Volume 2 litres
 Safety valve, 1.5 bar
 Connection: claw coupling
 (or 1"/R25 ext.)
 Temp 0-60 degrees
 Power: Max 9 kW
 Voltage 400 V 3N~ 50 Hz
 Current: 16 A
 Fuse: 3 x 16 A
 IP class: IP 44